



Agromehanika

SINCE 1968



AGP mounted mist blowers

300-500

300 I, 400 I, 500 I

Quality spraying with great savings

The development of modern plant protection machinery is governed by ever-increasing environmental protection awareness and growing demand for high-quality products. This prompted Agromehanika to develop a new family of mist blowers, AGP 300-500 EN, which comply with the most rigorous standards and at the same time facilitate the entire plant protection process.



Agromehanika d.d.

Hrastje 52A, 4000 Kranj, Slovenia

+386 4 23 71 300

agromehanika.si

sales@agromehanika.si

info@agromehanika.si



Agromehanika

SINCE 1968

AGP			200 EN	300 EN	400 EN	500 EN
Nominal tank volume		<i>l</i>	200	300	400	500
Dimensions	<i>Length</i>	<i>cm</i>	114	127	145	145
	<i>Width</i>	<i>cm</i>	96	105	127	127
	<i>Height</i>	<i>cm</i>	130	138	132	149
Weight		<i>kg</i>	148	211	235	242
Dimensions of the fan		<i>mm</i>	Ø 585	Ø 825		
Air quantity		<i>m³/h</i>	12000-32000	15000-45000		
Output air speed		<i>m/s</i>	< 40 (adjustable with a regulation of the heel of the fan blades)			
Spraying level		<i>m</i>	6			
Max. no. of revolutions of the fan		<i>n/min</i>	1800	1400		
Number of double nozzle holders			10	12		
Standard type of nozzle mountings			Lechler TR			
Type of the pump			Agromehanika BM 65/30 P: 73,30 l/min, max. 25 bar			
Tractor category			I. cat.		II. cat.	
Recommended power of the tractor		<i>kW</i>	22-40		35-72	
Recommended width/height of spraying		<i>m</i>	1,5-3,5/1-3	1,8-4/2-8		

AGP			200 ENU	300 ENU	400 ENU	500 ENU
Nominal tank volume		<i>l</i>	200	300	400	500
Dimensions	<i>Length</i>	<i>cm</i>	96	110	127	127
	<i>Width</i>	<i>cm</i>	120	134	151	151
	<i>Height</i>	<i>cm</i>	132	145	145	185
Weight		<i>kg</i>	151	225	249	271
Dimensions of the fan		<i>mm</i>	Ø 585/10	Ø 825/10 - 1300	Ø 825/14 - 1700	Ø 825/10 - 1300
Air quantity		<i>m³/h</i>	12000-32000	15000-45000		
Output air speed		<i>m/s</i>	< 40 (adjustable with a regulation of the heel of the fan blades)			
Max. no. of revolutions of the fan		<i>n/min</i>	1800	1400		
Number of double nozzle holders			10	10	14	14
Standard type of nozzle mountings			Lechler TR			
Tractor category			I. cat.		II. cat.	
Recommended power of the tractor		<i>kW</i>	22-40		35-72	