



AGS additional front tank

1500 F *1500I*


The Agromehanika AGS 1500F front tank with a capacity of 1500 liters is not just an ordinary tank with added volume. It offers innovative functionalities that go beyond mere capacity expansion. When combined with AGS mounted sprayers, it can achieve a total volume of approximately 2500-2700 liters, making it a serious competitor to trailed sprayers. It provides a comprehensive weight distribution solution that ensures optimal stability for your tractor. Managing the front tank is incredibly easy, thanks to the electric motor valves that you can operate directly from the tractor's cabin. For pumping and mixing, it is equipped with its own BM150 pump with hydraulic drive.

Agromehanika d.d.

Hrastje 52A, 4000 Kranj, Slovenia +386 4 23 71 300 agromehanika.si sales@agromehanika.si info@agromehanika.si







The AGS 1500 F front tank offers three possible uses:

- Increasing the capacity with the **same spraying agent** without the need to stop during spraying, as you can transfer the agent as needed during operation.
- Using **two different spraying agents**. Different agents can be mixed in the rear and front tanks.
- Using the front tank solely as a **clean water reservoir for later use** in another field or crop.

There is also an option to purchase the front tank **without a pump**, intended solely as an additional water reservoir. In this case, the **sprayer's pump takes care of the transfer**.

AGS		1500 F	1500 F additional
Tank capacity	I	1500	1500
Clear water tank capacity	1	100	100
Hand wash tank volume	1	10	10
Pump		BM 150	/
Pump capacity	I/min	146	/
Weight (empty)	kg	380	340
Dimensions (HxWxD)	cm	135x218x141	
Level indicator		mechanical	
Control		Through the electric panel from the cabin	manually
Transport wheels		Х	Х
Lights		X	Х