



Agromehanika

SINCE 1968



AGS trailed sprayers

2500-3000

15m, 18m, 21m, 24m

Quality protection for a high crop yield

Carefully structured, with an emphasis on design qualities and useful solutions, these sprayers enable you to work safely and efficiently. The circuit regulation system ensures the spraying is started immediately and provides for an even distribution across the entire surface. Thanks to the parallelogram hitch, the boom can be lifted even higher, while the Hydraulic drawbar ensures better wheel tracking. The sprayer also features a single-sided boom opening to help avoid any obstacles in the field.



Agromehanika d.d.

Hrastje 52A, 4000 Kranj, Slovenia

+386 4 23 71 300

agromehanika.si

sales@agromehanika.si

info@agromehanika.si



Agromehanika

SINCE 1968

AGS			2500				3000			
Booms			15m	18m	21m	24m	15m	18m	21m	24m
			HP	HP (X)	HP (X)	HP	HP	HP (X)	HP (X)	HP
Dimensions (boom included)	Length	cm	565	625	569	699	565	625	569	699
	Width	cm	220							
	Height	270/95 R38", cm	280							
		270/95 R44", cm	290							
	300/95 R46", cm	300								
Adjustable track		cm	150 - 220							
Clearance		270/95 R38", cm	60							
		270/95 R44", cm	70							
		300/95 R46", cm	80							
Sprayer and boom weight	Empty	kg	2320	2350	2391	2412	2330	2360	2401	2422
	Full	kg	5150	5180	5221	5240	5660	5690	5731	5752
Number of sections			7							
TRI-JET nozzle holders		pcs	30	36	42	48	30	36	42	48
Distribution of nozzles by sections			2-4-7-4-7-4-2	5-4-7-4-7-4-5	5-6-8-4-8-6-5	6-8-8-4-8-8-6	2-4-7-4-7-4-2	5-4-7-4-7-4-5	5-6-8-4-8-6-5	6-8-8-4-8-8-6
Nozzle height		270/95 R38"	35 - 225							
		270/95 R44"	45 - 235							
		300/95 R46"	55 - 245							

