



# Agromehanika

SINCE 1968



*AGT tractors*

# 1060

*STAGE 5*

## *The right answer to modern demands*

AGT tractors are designed to make it easy for the user to perform complex tasks in agriculture and horticulture. Numerous technical features also make them suitable for amenity work, ground care work and forestry. Thanks to its rigid chassis, small turning circle, permanent 4-wheel drive and a low centre of gravity, they are also suitable for use in mountainous areas. The tractors are distinguished by the 'bi-directional' reversible driving position. This allows the user complete control over the direction of work. The new AGT 1060 tractor features a new EURO 5 emission engine and powerful hydraulic system.



## Agromehnika d.d.

Hrastje 52A, 4000 Kranj, Slovenia

+386 4 23 71 300

agromehnika.si

sales@agromehnika.si

info@agromehnika.si



## Agromehnika

SINCE 1968

AGT		1060					
<b>Chassis</b>		Rigid design 15 ° / 15 ° front axle tilt - Permanent 4-wheel drive - Hydraulic steering - Internal turning circle min. 360 cm					
<b>Engine</b>		Kohler KDI 1903 TCR					
<b>Type</b>		4-stroke diesel engine					
<b>Manufacturer</b>		Kohler					
<b>Designation</b>		KDI 1903 TCR					
<b>Cooling</b>		Water					
<b>Engine power</b>	<i>kW/hp</i>	42 / 56					
<b>Max. torque</b>	<i>Nm</i>	225 / 1500					
<b>Volume</b>	<i>cm<sup>3</sup></i>	1861					
<b>No. of cylinders</b>		3 - turbo common rail					
<b>Emissions</b>		STAGE 5					
<b>Max. No. of rotations</b>	<i>rpm</i>	2600					
<b>Fuel tank</b>	<i>l</i>	37					
<b>Gearbox</b>		Synchronised, 24 gears (12 forward and 12 backwards with shuttle)					
<b>PTO</b>		540/ 750/ synchronized with the gearbox and fully independent, electric-magnetic activation.					
<b>Rear linkage</b>		Hydraulic, 3-point hitch, cat. I, lifting force 1300 kg					
<b>Hydraulic valves</b>		Standard - single block with 3 sections and 4 quick couplings, optional additional block on the left side and a total of 10 quick couplings					
<b>Hydraulic pump</b>		Steering wheel and operational (4+11), max. flow 33 l/min,					
<b>Differential lock</b>		Front and rear axle, electric-magnetic activation					
<b>Brakes</b>		Hydraulically operated, oil immersed discs on all four axles					
<b>Dimensions</b>		Standard version				Wide version	
<b>Wheels</b>		7,5-16	260/70 R16	280/70 R18	31x15,50-15	31x15,50-15	280/70 R18
<b>Width</b>	<i>mm</i>	1266-1542	1421-1567	1394-1470	1580	1920	1750
<b>Length</b>	<i>mm</i>	3290-3550					
<b>Height</b>	<i>mm</i>	2101	2084	2124	2108	2108	2124

